

Galvanized conductive TPR wheels

商品介紹 Product description



[JZ-206-1S]

- 1.一體拉伸成型支架。
- 2.雙層滾珠設計。
- 3.全覆式防塵蓋。

- 材質：單軸承塑芯TPR輪
- 用途：工業、物流台車、重型機械設備、常用於各式推車及台車

1. One-piece stretch forming bracket.
2. Double-layer ball design.
3. Full-coverage dust cover.

- Material: Single bearing plastic core TPR wheel
- Uses: Industrial, logistics trolleys, heavy machinery equipment, commonly used in various carts and trolleys.



[JZ-206-1R]



[JZ-206-1H]



[JZ-206-2S]



[JZ-206-2H]



[JZ-206-3H]



[JZ-206-3S]

商品型號	輪子	輪徑	輪寬	安裝高度	底板尺寸	孔距	孔徑	荷重 (KG)
JZ-206-1-1_	導電 TPR	40	25	61	70*51	52*35	8.5	30
JZ-206-1-2_		50		75.5				40
JZ-206-1-3_		63		92				50
JZ-206-1-4_		75		101				60

JZ-206-1系列可選配R固定/S活動/H煞車

商品型號	輪子	輪徑	輪寬	安裝高度	牙桿尺寸	荷重 (KG)
JZ-206-2-1_	導電 TPR	40	25	63	M10*25	30
JZ-206-2-2_		50		77.5		40
JZ-206-2-3_		63		94		50
JZ-206-2-4_		75		103		60

JZ-206-2系列可選配S活動/H煞車

商品型號	輪子	輪徑	輪寬	安裝高度	孔頂尺寸	荷重 (KG)
JZ-206-3-1_	導電 TPR	40	25	59	Ø10.2	30
JZ-206-3-2_		50		73.5		40
JZ-206-3-3_		63		90		50
JZ-206-3-4_		75		99		60

JZ-206-3系列可選配S活動/H煞車